

JUN 24 2009 08:48AM P3
JUN 24 2009Akiko SHINOHARA et al., S.N. 10/521,978
Page 2

Dkt. 1141/73755

Listing of Claims

The following listing of claims will replace all prior versions, and listings, of claims in the subject application:

1. (currently amended) A medical image diagnosis apparatus which images a subject by forming a whole image of a subject portion of the subject, displays imaging conditions on the whole image, and allows an operator to set or modify the imaging conditions for ~~obtaining~~ imaging a tomographic image ~~of the subject portion under the imaging conditions~~, the medical image diagnosis apparatus comprising:

a first display device for displaying the whole image and the imaging conditions including a frame indicating a scan area and lines indicating imaging ~~position~~ positions of ~~[[the]]~~ tomographic images and image reconstruction positions of the tomographic images;

a second display device for extracting one or more of the imaging conditions including the frame and the lines and displaying the extracted imaging conditions for imaging the tomographic images;

a display control device for the first display device and the second display device; and

an operating device for ~~variably inputting~~ setting or changing the imaging conditions for imaging the tomographic images, which includes by adjusting the frame and the lines displayed by the second display device.

2. (original) The medical image diagnosis apparatus according to claim 1, wherein the imaging conditions displayed on the first and second display device are imaging conditions displayed by graphic display and including at least one of an imaging position, an imaging area,

Akiko SHINOIARA et al., S.N. 10/521,978
Page 3

Dkt. 1141/73755

a certain number of instances of image reconstruction, an image reconstruction position and a scanner angle.

3. (original) The medical image diagnosis apparatus according to claim 1, wherein the imaging conditions displayed on the second display device further include imaging sequence ordinal numbers for setting the imaging conditions with respect to each of a plurality of imaging sequences.

4. (original) The medical image diagnosis apparatus according to claim 1, wherein a display frame on the first display device and the display frame on the second display device share one monitoring screen.

5. (original) The medical image diagnosis apparatus according to claim 1, wherein display devices for the first display device and the second display device are provided separately from each other.

6. (original) The medical image diagnosis apparatus according to claim 3, wherein at least one of the imaging conditions for imaging varies among the imaging sequences.

7. (original) The medical image diagnosis apparatus according to claim 3, wherein the desired order of execution of the plurality of imaging sequences is designated by inputting numeric values.

Akiko SHINOHARA et al., S.N. 10/521,978
Page 4

Dkt. 1141/73755

8. (original) The medical image diagnosis apparatus according to claim 2, wherein the imaging position and the imaging area in the imaging conditions are indicated by a rectangular frame and a mark in the rectangular frame in the first display device and the second display device, and are set in at least one of the first display device and the second display device.

9. (original) The medical image diagnosis apparatus according to claim 8, wherein the number of instances of image reconstruction and the image reconstruction positions in the imaging conditions are indicated by lines provided in the rectangular frame and dividing the rectangular frame by extending parallel to sides of the rectangular frame, and are set in at least one of the first display device and the second display device.

10. (original) The medical image diagnosis apparatus according to claim 8, wherein the operating device can extend or contract the rectangular frame in any direction, and move the mark to any position together with the rectangular frame.

11. (original) The medical image diagnosis apparatus according to claim 9, wherein the operating device can generate the division lines in the rectangular frame at any position and move the division lines to any position.

12. (previously presented) The medical image diagnosis apparatus according to claim 8, wherein the operating device can form a parallelogram by tilting the rectangular frame indicated in the first display device and the second display device, and set the scanner angle in the imaging conditions as the tilt angle of the parallelogram in the first display device and the second display

Akiko SHUNOHARA et al., S.N. 10/521,978

Dkt. 1141/73755

Page 5

device.

13. (previously presented) The medical image diagnosis apparatus according to any one of claims 8 to 12, wherein the rectangular frame, the division lines and the mark can be moved or copied from the first display device to the second display device or between the first display device and the second display device in an identical, similar or analogous form.

14. (original) The medical image diagnosis apparatus according to any one of claims 4 to 12, wherein the operating device comprises a pointer.

15. (original) The medical image diagnosis apparatus according to any one of claims 1 to 3, wherein the second display device comprises a touch panel.

16. (currently amended) A medical image diagnosis apparatus which forms a whole image of a subject portion of a subject and obtains one or more tomographic images under imaging conditions for imaging a tomographic image ~~set based on the whole image~~, the medical image diagnosis apparatus comprising:

a first display device for displaying the whole image of the subject portion and the imaging conditions including a frame indicating a scan area and lines indicating imaging ~~position~~ positions of the tomographic images and image reconstruction positions of the tomographic images;

a second display device for extracting one or more of the imaging conditions including the frame and the lines and displaying the imaging ~~condition~~ conditions including the frame

Akiko SHINOHARA et al., S.N. 10/521,978

Dkt. 1141/73755

Page 6

and the lines extracted from the first display device for setting the imaging conditions for obtaining the one or more tomographic images;

an operating device for an operator to selectively set the imaging conditions for imaging the tomographic images, by adjusting ~~utilizing~~ the frame and the lines displayed by said second display device; and

a display control device for displaying, on the whole image displayed on the first display device, information indicating positions of said one or more tomographic images to be obtained ~~on the whole image displayed on the first display device,~~ based on the imaging conditions set with the operating device.